

ACID WASH 201

HEAVY-DUTY ACID CLEANER

ACIDS



ACID WASH 201 is a heavy-duty, inhibited acid cleaner designed for cleaning and brightening aluminum as well as for removing tough oxidation and scale build-up from various metals. It effectively removes stubborn environmental contaminants such as brake and rail dust from rims, side rails, paint and other surfaces as well as dislodges tough silicate scale build-ups or clay accumulations.

FEATURES AND BENEFITS

- Non-chelating blend of dilute mineral acids with added corrosion inhibitor
- Low foaming
- · Contains added surfactant for uniform surface wetting
- Concentrate formula available with the product ACID WASH 200
- Very rapid action
- May be used as a "fallout" or rail dust remover for vehicles transported by train
- Effective on tough scale build-ups
- Rapid and uniform wetting properties prevents localized pitting and corrosion

DIRECTIONS FOR USE

Use procedure

Use **ACID WASH 201** as part of a low-pressure application. Most effective when used with soft water. Scour or brush stubborn deposits.

Concentration

For all applications, dilute at maximum of 7% v/v with water. Not recommended for use at full concentration.

Use temperature

Cold water is recommended.

Dwell time / Operation time

Allow to dwell 3 to 5 minutes before final rinsing.

Mechanical action

Low pressure application and rinsing recommended for removing stubborn deposits.

Rinsing

High pressure water.

ACID WASH 201

HEAVY-DUTY ACID CLEANER

PHYSICAL PROPERTIES

Appearance	Red liquid
Odour	Pungent
Specific Gravity @ 20°C	1.080-1.090
Viscosity	Thin
рН	<1.0
Flash Point (TCC)	None
Boiling Point	Approx. 100°C (212°F)
Freezing Point	-5°C (23°F)
Foaming Tendency	Low
Concentration Monitoring Techniques	Not determined
Rinsability	Excellent
Water Solubility	Complete

INCOMPATIBILITY

Chlorinated, strong oxidizing or alkaline materials

Avoid prolonged contact with mild or galvanized steel

Do not use on glass

WAREHOUSING PRECAUTIONS

Keep from freezing Keep container closed when not in use

AVAILABLE SIZES			
	20L / 5,28Gal.	205L / 54,16Gal	

FIRST AID MEASURES

EYE CONTACT: Flush with plenty of water for 15 minutes. Apply 1 or 2 drops of pontocaine hydrochloride solution followed by a second 15 minute rinse. Contact physician immediately. **SKIN CONTACT:** Flush with plenty of water for 15 minutes. Consult physician. Soak affected area in Hyamine 1622, 0.2% solution or apply calcium gluconate gel.

INHALATION: Get to fresh air. Consult physician immediately.

INGESTION: Do not induce vomiting. Drink plenty of water and contact physician

immediately.

HEALTH	2
FLAMMABILITY	0
REACTIVITY	0

REACTIVITY 0

LEGEND
0 = MINIMAL RISK
1 = SLIGHT RISK
2 = MODERATE RISK
3 = SERIOUS RISK
4 = SEVERE RISK

PERSONAL PROTECTION Security equipment

WHMIS

IMPORTANT: Before using ACID WASH 201, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



MONTRÉAL

10,900 rue Sécant Anjou, QC H1J 1S5 Tel.: 514-355-4660 Toll free : 1-800-361-8927

EDMONTON

11411-160 Street Edmonton, Alberta T5M 3T7 Tel.: 780-454-3919

Toll free: 1-866-454-3919 www.westpenetone.com