

### H<sub>2</sub>S SCAVENGERS / DEGASIFICATION



**ELIMINATOR** is a non-corrosive, fast-acting hydrogen sulfide gas scrubbing solution. It removes hydrogen sulfide from the gaseous phase to control headspace emissions or regulate contaminated gas streams for safe fluid transport and remedial operational or repair work.

### FEATURES AND BENEFITS

- Non-corrosive
- Fast acting
- Contains no added formaldehyde
- High capacity gas scrubbing formula, utilizing added formaldehyde, available in **PENETONE 8507H**
- Gas phase capacity tested under Alberta Sulphur Research high hydrogen sulphide flow scavenger test method

### DIRECTIONS FOR USE

<b>Chemical type</b>	Triazine derivative.
<b>Use procedure</b>	For optimum results, use <b>ELIMINATOR</b> at full concentration via spray or in a gas scrubber system.
<b>Minimum treatment guidelines</b>	Removes 0.09 kg or approximately 0.2 lb of H <sub>2</sub> S in headspace gas per liter (0,27 gal.). 0.02 mL treats 1 ppm H <sub>2</sub> S per 1 m <sup>3</sup> (0.02 oz treats 1 ppm per ft <sup>3</sup> ) of contaminated gas by flow rate for continuous treatment and reaches saturation at approx. 0.20-0.22 lb of sulfur per L (0,27 gal.) of product in scrubbing applications.
<b>Gas removal guidelines</b>	Adjust flow rate to reduce H <sub>2</sub> S breakthrough when utilizing a fresh solution. Overall flow-rate and H <sub>2</sub> S concentration will affect treatment rate and product longevity.
<b>Additional guidelines</b>	Scrubber can be rinsed with methanol, glycols, or water once scrubbing solution has been spent. Flood scrubber with <b>OXYBRITE SB 1.5</b> after rinsing to remove any remaining solids accumulation.

# ELIMINATOR

## HYDROGEN SULFIDE GAS SCRUBBING SOLUTION

### PHYSICAL PROPERTIES

Appearance	Yellow liquid
Odour	Alcohol/amine
Specific Gravity @ 20°C	0.950-0.970
Viscosity	Thin
pH	9.5-10.5
Flash Point (TCC )	24°C (72,5°F)
Boiling Point	Not determined
Freezing Point	Approx. -35°C (-31°F)
Foaming Tendency	Moderate
Concentration Monitoring Techniques	pH
Water Solubility	Complete

### INCOMPATIBILITY

Oxidizing materials,  
strong acids and bases

### WAREHOUSING PRECAUTIONS

Keep container closed when not in use  
Store away from heat sources and flames

### AVAILABLE SIZES

			
20L/ 5,28Gal.	205L/ 54,16Gal.	1000L/ 264,71Gal.	

### FIRST AID MEASURES

#### EYE CONTACT

Wash with plenty of water for 15 minutes.  
Consult physician if irritation develops or persists.

#### SKIN CONTACT

Wash with plenty of water for 15 minutes.  
Consult physician if irritation develops or persists.

#### INHALATION

Give fresh air or artificial respiration. Consult physician.

#### INGESTION

Administer 1-2 glasses of water. Induce vomiting.  
Seek medical attention. Never administer fluids to an unconscious person.

### HEALTH

2

### FLAMMABILITY

3

### REACTIVITY

0

#### LEGEND

0 = MINIMAL RISK  
1 = SLIGHT RISK  
2 = MODERATE RISK  
3 = SERIOUS RISK  
4 = SEVERE RISK

### PERSONAL PROTECTION Security equipment



WHMIS



**IMPORTANT:** Before using ELIMINATOR, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S.).



#### CARLSTADT

700 Gotham Parkway  
Carlstadt, New Jersey 7072  
Tel.: 201-567-3000  
Toll free : 1-800-631-1652

#### MONTREAL

10,900 rue Secant  
Anjou, QC H1J 1S5  
Tel.: 514-355-4660  
Toll free : 1-800-361-8927

#### EDMONTON

11411-160 Street  
Edmonton, Alberta T5M 3T7  
Tel.: 780-454-3919  
Toll free: 1-866-454-3919

United States  
[www.penetone.com](http://www.penetone.com)

Canada  
[www.westpenetone.com](http://www.westpenetone.com)