

SOLVENT DEGREASERS



RAMEX is an economical solvent blend designed for continuous heavy duty manual tasks. It is ready to use for removing deposits such as tar, heavy crudes, and carbonized hydrocarbons from a variety of surfaces while employing a higher content of high distillate grade aliphatic material for longer residence time and less evaporative loss.

FEATURES AND BENEFITS

- Disperses hydrocarbon sludge and foulant accumulation upon application and rinsing
- Cost efficient alternative to the product **RAMSOL**
- Powerful and fast acting
- Ready to use
- Safe on all hard metal surfaces
- Rinses effectively leaving little to no residue
- May be used in cold dip tank or parts washer applications
- Provides longer dwell time for improved foulant removal

DIRECTIONS FOR USE

Soils to be removed	Tar, grease, bitumen residue, oils, carbonized deposits, etc.
Use procedure	Use RAMEX as part of a manual, low-pressure, or cold dip tank application. For very thick accumulations, physically remove excess or loose deposits before application.
Concentration	Most effective when used undiluted. Dilute 15-20% v/v with a suitable solvent such as diesel, Varsol, or TPC SOLVENT for cold dip tank applications.
Dwell time / Operation time	5 to 30 minutes, according to the amount of soil.
Mechanical action	Scrubbing and wiping recommended to remove stubborn deposits.
Rinsing	Allow product to dwell before rinsing. High-pressure, hot water is recommended.

RAMEX

HEAVY-DUTY ECONOMICAL SOLVENT CLEANER

PHYSICAL PROPERTIES

Appearance	Yellow liquid
Odour	Solvent
Specific Gravity @ 20°C	0.80-0.81
Viscosity	Thin
pH	Not applicable
Flash Point (TCC)	49°C (120,2°F)
Boiling Point	Not determined
Freezing Point	-34°C (-29,2°F)
Foaming Tendency	Nil
Rinsability	Excellent
Water Solubility	Nil




INCOMPATIBILITY

Oxidizing materials
Do not use on finely coated surfaces

WAREHOUSING PRECAUTIONS

Keep container closed when not in use
Store away from heat sources and flames

AVAILABLE SIZES

		
20L / 5,28Gal.	205L / 54,16Gal	1000L / 264,17Gal.

FIRST AID MEASURES

EYE CONTACT

Wash with plenty of water for 15 minutes.
Contact physician if irritation persists or develops or persists.

SKIN CONTACT

Wash with plenty of water for 15 minutes.
Consult physician if irritation develops or persists.

INHALATION

Give fresh air or artificial respiration.
Consult physician.

INGESTION

Do not induce vomiting. Drink plenty of water and contact physician immediately.

HEALTH

2

FLAMMABILITY

2

REACTIVITY

0

LEGEND

0 = MINIMAL RISK
1 = SLIGHT RISK
2 = MODERATE RISK
3 = SERIOUS RISK
4 = SEVERE RISK

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using RAMEX, always be sure to read and follow precautions and directions for use appearing on the product container label and on the material safety data sheet (m.s.d.s.).

MONTRÉAL

10,900 rue Sécant
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free : 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919