

# **RAMSOL BCX**

## HEAVY-DUTY SOLVENT DEGREASER

### SOLVENT DEGREASERS



**RAMSOL BCX** is a heavy duty solvent blend designed for chemical circulation procedures where the removal of asphaltenes and resins is required from lines and vessels. It can be emulsified in water to a low or high pH to customize foulant removal.

#### FEATURES AND BENEFITS

- Disperses hydrocarbon sludge and foulant accumulation upon application and rinsing
- · Powerful and fast acting
- · Safe on all hard metal surfaces
- Effective and efficient replacement for hot diesel cleaning

## **DIRECTIONS FOR USE**

Soils to be removed

Use procedure

Saturates & polymeric materials, bitumen, resins, heavy oils, asphaltenes, etc.

May be used in combination with alkali, acid, and surfactant chemical cleaning or circulation procedures. Rinse procedure recommended.

Consult with your local West Penetone sales representative for procedures best suited for your application.

Most effective when used undiluted.

Dilute to 2-5% v/v when used as part of a general chemical cleaning procedure requiring film removal. For removal of heavy deposition, use up to 18-25% v/v.

Ambient when used at concentrate. 65°C-70°C (149°F-158°F) recommended when used as part of chemical cleaning procedure.

5 to 30 minutes, according to the amount and depth of foulant. Monitoring and centrifuging of retains is recommended.

Concentration

**Use Temperature** 

**Dwell time / Operation time** 

# **RAMSOL BCX**

## Heavy-duty solvent degreaser

#### **PHYSICAL PROPERTIES**

Appearance	Yellow liquid
Odour	Solvent/pine
Specific Gravity @ 20°C	0.895 - 0.900
Viscosity	Thin
рН	Not applicable
Flash Point (TCC)	46°C (114,8°F)
Boiling Point	Not determined
Freezing Point	Not determined
Foaming Tendency	Nil
Concentration Monitoring Techniques	Not determined
Rinsability	Excellent
Water Solubility	Emulsifies

#### **INCOMPATIBILITY**

Oxidizing materials Do not use on finely coated surfaces

#### **WAREHOUSING PRECAUTIONS**

Store away from heat sources and flames

AVAILABLE SIZES				
	20L / 5,28Gal.	205L / 54,16Gal	1000L / 264,17Gal.	

## **FIRST AID MEASURES**

#### **EYE CONTACT**

Wash with plenty of water for 15 minutes. Consult physician if irritation develops or persists.

#### **SKIN CONTACT**

Wash with plenty of water for 15 minutes. Consult physician if irritation develops or persists.

#### **INHALATION**

Give fresh air or artificial respiration. Consult physician.

#### **INGESTION**

Do not induce vomiting. Drink plenty of water and consult physician immediately.

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0

#### LEGEND

- 0 = MINIMAL RISK
- 1 = SLIGHT RISK
- 2 = MODERATE RISK
- 3 = SERIOUS RISK
- 4 = SEVERE RISK



IMPORTANT: Before using RAMSOL BCX, always be sure to read and follow precautions and directions for use appearing on the product container label and on the material safety data sheet (m.s.d.s.).



#### **MONTRÉAL**

10,900 rue Sécant Anjou, QC H1J 1S5 Tel.: 514-355-4660 Toll free: 1-800-361-8927

#### **EDMONTON**

11411-160 Street Edmonton, Alberta T5M 3T7 Tel.: 780-454-3919 Toll free: 1-866-454-3919

www.westpenetone.com