

**SOLVENT DEGREASERS**



**RAMSOL** is a heavy-duty aromatic blend designed for a variety of demanding degreasing applications. It removes a variety of stubborn deposits such as bitumen or bituminous residues, asphaltenes, resins, and petroleum waxes quickly and effectively while minimizing residual filming, common with solvent cleaners, where rinse procedures are employed or required.

**FEATURES AND BENEFITS**

- Heavy-duty aromatic blend
- Contains added detergent and emulsifier to further mobilize deposits and reduce residual filming where rinse procedures are applied
- Powerful and fast acting
- Safe on all hard metal surfaces
- Removes a multitude of soils including petroleum-based materials, adhesives, inks, and other water-insoluble deposits such as waxes

**DIRECTIONS FOR USE**

<b>Surface to be cleaned</b>	Exterior of road vehicles, equipment, interior of storage tanks, etc.
<b>Soils to be removed</b>	Saturates & polymeric materials, bitumen, waxes, asphaltenes, etc.
<b>Use procedure</b>	Use <b>RAMSOL</b> as part of a manual or low-pressure application. For very thick accumulations, physically remove excess or loose deposits before application. May also be used as an additive in dip tank applications.
<b>Concentration</b>	Most effective when used undiluted. Dilute up to 20% v/v with a suitable solvent such as diesel for all manual, low-pressure and dip tank applications.
<b>Dwell time / Operation time</b>	5 to 30 minutes, according to the amount of soil.
<b>Mechanical action</b>	Scrubbing and wiping recommended to remove stubborn deposits.
<b>Rinsing</b>	Allow product to dwell before rinsing. High-pressure, hot water is recommended.

# RAMSOL

## HEAVY-DUTY SOLVENT CLEANER

### PHYSICAL PROPERTIES

Appearance	Yellow Liquid
Odour	Solvent
Specific Gravity @ 20°C	0.870-0.900
Viscosity	Thin
pH	Not applicable
Flash Point (TCC)	41°C (105,8°F)
Boiling Point	140.8°C (284°F)
Freezing Point	Approx. -34°C (-29,2°F)
Foaming Tendency	Nil
Concentration Monitoring Techniques	Not determined
Rinsability	Excellent
Water Solubility	Nil




### INCOMPATIBILITY

Oxidizing materials  
Do not use on finely coated surfaces

### WAREHOUSING PRECAUTIONS

Keep container closed when not in use  
Store away from heat sources and flames

### AVAILABLE SIZES

		
20L / 5,28Gal.	205L / 54,16Gal	1000L / 264,17Gal.

### FIRST AID MEASURES

#### EYE CONTACT

Wash with plenty of water for 15 minutes.  
Consult physician if irritation develops or persists.

#### SKIN CONTACT

Wash with plenty of water for 15 minutes.  
Consult physician if irritation develops or persists.

#### INHALATION

Give fresh air or artificial respiration.  
Consult physician.

#### INGESTION

Do not induce vomiting. Drink plenty of water and consult physician immediately.

### HEALTH

2

### FLAMMABILITY

2

### REACTIVITY

1

#### LEGEND

0 = MINIMAL RISK  
1 = SLIGHT RISK  
2 = MODERATE RISK  
3 = SERIOUS RISK  
4 = SEVERE RISK

### PERSONAL PROTECTION Security equipment



WHMIS



**IMPORTANT:** Before using RAMSOL, always be sure to read and follow precautions and directions for use appearing on the product container label and on the material safety data sheet (m.s.d.s.).