

FOOD INDUSTRY



Food and beverage
industry accepted

VEGETOL HA is a mix of vegetable and mineral oils, specially designed for food processing equipment. Can be used as corrosion inhibiting film for mild or galvanized steel surfaces or to improve the appearance of stainless steel or plastic.

FEATURES and BENEFITS

- High viscosity
- Odourless
- Approved by Agriculture Canada
- Its high viscosity allows **VEGETOL HA** to cling to surfaces.
- Easy to apply with a manual or pump spray.
- Does not drip even when applied repeatedly.
- Easy to remove with usual cleaning methods

DIRECTION FOR USE

Spray **VEGETOL HA** onto clean and dry surface with compressed or other type of air sprayer.

It is recommended to apply only the quantity needed to cover the surface to avoid dripping.

Allow to dwell until next cleaning

VEGETOL HA

PROTECTIVE FILM AND LUBRICANT

PHYSICAL PROPERTIES

Appearance	Light yellow liquid
Odour	None
Specific gravity @ 20 °C	0.88 - 0.89
Viscosity	310-330 SUS
pH	Not applicable
Flash point (TCC)	Above 218 °C
Pour point	-18
Water solubility	Insoluble
Auto ignition temperature	None
Chlorine	None
Boiling point	Not available
Freezing point	Not available
Foaming tendency	Non-foaming
Concentration monitoring techniques	Not available
Rinsing	Poor

INCOMPATIBILITY

Strong oxidizers

WAREHOUSING PRECAUTIONS

None

FIRST AID MEASURES

EYE CONTACT

Wash with plenty of water for 15 minutes. Consult physician if irritation develops or persists.

SKIN CONTACT

Wash with soap and water.

INHALATION

No object

INGESTION

Do not induce vomiting. Drink plenty of water and contact physician.

HEALTH

0

FLAMMABILITY

0

REACTIVITY

0

LEGEND

0 = MINIMAL RISK
1 = SLIGHT RISK
2 = MODERATE RISK
3 = SERIOUS RISK
4 = SEVERE RISK

PERSONAL PROTECTION Security equipment

WHMIS

IMPORTANT : Before using **VEGETOL HA**, always be sure to read and follow precautions and directions for use appearing on the product's container label, and on the safety data sheet (S.D.S).