

ACCUSOLVE 875

SAFETY DATA SHEET

Page 1 of 7

ACCUSOLVE 875 SDS GHS

1. IDENTIFICATION

Product Identifier Product Name Chemical Name

ACCUSOLVE 875 Solvent blend

Recommended use of the chemical and restrictions on use

Recommended use Restrictions on use Degreaser For industrial use only

Supplier details

West Penetone Inc. 11411-160 Street Edmonton, AB, T5M3T7 Tel: 780-454-3919

Emergency Telephone Number

(780) 454-3919 (Mon - Fri, 8 AM - 4:30 PM, Mountain time)

2. HAZARDS IDENTIFICATION

Classification

Flammable liquids	Category 3
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Aspiration hazard	Category 1
Carcinogenicity	Category 1B
Germ cell mutagenicity	Category 1B
Specific Target Organ Toxicity: Single Exposure (Respiratory, Central Nervous System)	Category 3

Label Elements

DANGER

Flammable liquid and vapor Causes skin irritation. Causes serious eye damage. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. May cause respiratory irritation. May cause cancer. May cause genetic defects.

Precautionary Statements - Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Keep away from heat, sparks, open flames, and hot surfaces. No smoking.

Keep container tightly closed. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use explosion-proof electrical equipment and use only non-sparking tools.

Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink, or smoke when using this product.

Use only outdoors or in a well-ventilated area. Avoid breathing fume, mist, vapors, or spray

ACCUSOLVE 875 SDS GHS

Wear protective gloves, protective clothing, and eye protection or face protection.

Precautionary Statements - Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. IF SKIN irritation occurs: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use carbon dioxide, foam, or dry chemical to extinguish.

Precautionary Statements - Storage

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant according to local, provincial/federal regulations.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight %
Stoddard solvent	8052-41-3	30 - 60*
Benzene, C6-12-alkyl derivatives	68608-80-0	10 – 30*
Diethylene glycol monobutyl ether	112-34-5	10 – 30*
Xylene	1330-20-7	3 – 7*
Cocoamide diethanolamine	68603-42-9	3 – 7*
Sodium docusate	577-11-7	3 – 7*

*Actual concentration is withheld as a trade secret

Stoddard Solvent (CAS 8052-41-3) contains the following hazardous components:

Chemical Name	CAS No	Weight %
Ethyl benzene	100-41-4	0.1 – 0.5
Naphthalene	91-20-3	0.1 – 0.5
Nonane	111-84-2	1 – 5
Pseudocumene (1,2,4-Trimethylbenzene)	95-63-6	1 – 5
Toluene	108-88-3	0.1 – 1

4. FIRST AID MEASURES

Ingestion:	Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician immediately.
Skin contact:	Wash with plenty of water. Take off contaminated clothing and wash before reuse. If skin irritation occurs, get medical advice/attention.
Inhalation:	If difficulties occur after mist/vapors/spray has been inhaled, remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Eye contact:	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice if eye irritation occurs.

Most important symptoms and effects, both acute and delayed.

Contact with eyes may cause serious damage or irritation leading to discomfort, redness, swelling or blindness. Contact with skin may cause irritation with local redness and possible dermatitis shortly after exposure. Inhalation of vapors may cause drowsiness or dizziness, headaches, fatigue, muscular weakness and in extreme cases, loss of consciousness. Inhalation of vapors may cause irritation of the respiratory system. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion may cause pneumonitis or pulmonary edema if aspirated.

Indication of any immediate medical attention and special treatment needed.

Treat symptomatically.

ACCUSOLVE 875 SDS GHS

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use water fog, foam, dry chemical, or carbon dioxide to extinguish flames.

Unsuitable Extinguishing Media

Do not use water jet.

Specific hazards arising from the chemical.

During fire, gases hazardous to health may be formed including oxides of carbon, nitrogen and sulfur.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Use personal protective equipment.

Environmental Precautions

Avoid discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up.

Contain and solidify with inert absorbent materials. Keep in suitable, closed containers for disposal. Following product recovery, flush area with water. For large spills, stop flow of material, prevent product from entering drains, and pump off product where this is without risk and possible. Proceed as above.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Handling: Avoid inhalation of fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing. Ensure thorough ventilation of work areas. Use personal protective equipment. Use proper bonding or ground procedures. Keep away from sources of ignition. Smoking should be prohibited in the application area

Conditions for safe storage, including any incompatibilities

 Storage:
 Keep containers tightly closed away in a dry, cool and well-ventilated place, away from incompatible materials.

Incompatible Materials:

Strong oxidizing agents and concentrated mineral acids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Only constituents with exposure limits are listed. Any constituent not listed has no known exposure limit.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Stoddard solvent CAS 8052-41-3	TWA: 100 ppm	Not available	Not available
Benzene, C6-12-alkyl derivatives CAS 68608-80-0	>5000 mg/kg (rat)	>5000 mg/kg (rat)	Not listed
Diethylene glycol monobutyl ether CAS 112-34-5	TWA: 10 ppm	Not Available	Not Available
Ethyl benzene CAS 100-41-4	TWA: 20 ppm	Not available	Not available
Naphthalene CAS 91-20-3	TWA: 10 ppm	TWA: 10 ppm/ 50 mg/m ³ STEL: 15 ppm	Not Available
Nonane CAS 111-84-2	TWA: 200 ppm	Not available	Not Available
Trimethylbenzenes CAS 526-73-8, 95-63-6, 108-67-8	TWA: 25 ppm/123 mg/m ³	Not available	Not available
Toluene CAS 108-88-3	TWA: 20 ppm	TWA: 100 ppm STEL: 150 ppm	Not Available

Appropriate	engineering	controls
Appropriate	engineering	001101010

Engineering Controls: Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face Protection:Safety glasses with side shields or goggles. Use a face-shield where mode of handling
increases risk of splashing.Skin and body protection:Wear protective gloves and protective clothing.Respiratory Protection:Wear respiratory protection if ventilation is inadequate.General Hygiene Considerations:Handle in accordance with good industrial hygiene and safety practice. Routinely wash work
clothing and protective equipment to remove contaminants.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colourless or yellow-brown liquid ODOR: Petroleum ODOR THRESHOLD: Not available pH: Not applicable MELTING POINT / FREEZING POINT: Not available **BOILING POINT/BOILING RANGE:** Approximately 148 °C to 300 °C FLASH POINT: >38°C / >100°F EVAPORATION RATE, water = 1: >1 FLAMMABILITY (SOLID, GAS): Not applicable

VAPOR PRESSURE, mm Hg AT 20°C: Not available VAPOR DENSITY (Air = 1): Not available **RELATIVE DENSITY AT 20°C:** 0.850 - 0.870SOLUBILITY IN WATER: insoluble PARTITION COEFFICIENT, N-OCTANOL/WATER: Not available **AUTO-IGNITION TEMPERATURE:** Approx. 260 °C **DECOMPOSITION TEMPERATURE:** Not available VISCOSITY: Not available FLAMMABLE LIMITS: Not available

ACCUSOLVE 875 SDS GHS

10. STABILITY AND REACTIVITY

Reactivity

Not reactive.

<u>Chemical Stability</u> Stable under normal conditions.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to Avoid

Avoid extreme temperatures. Store away from incompatible materials.

Incompatible Materials

Strong oxidizing materials and concentrated mineral acids.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition can lead to release of irritating gases and vapors such as oxides of carbon as well as other low molecular weight hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

<u>ATE_{mix}</u> – LD50 oral >2000 mg/kg, LD50 dermal >2000 mg/kg, LC50 inhalation >5 mg/L Not classified as an acutely toxic mixture.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Stoddard solvent CAS 8052-41-3	>5000 mg/kg (rat)	>3000 mg/kg (rabbit)	> 13.1 mg/L vapour, 4 h (rat)
Benzene, C6-12-alkyl derivatives CAS 68608-80-0	>5000 mg/kg (rat)	>5000 mg/kg (rat)	Not listed
Diethylene glycol monobutyl ether CAS 112-34-5	>4500 mg/kg (rat)	>2764 mg/kg (rabbit)	>29 ppm, 2 h (rat)
Cocoamide diethanolamine CAS 68603-42-9	>2000 mg/kg (rat)	>2000 mg/kg (rabbit)	Not listed
Sodium docusate CAS 577-11-7	2881mg/kg (rat)	5610mg/kg (rat)	Not listed
Ethyl benzene CAS 100-41-4	3500 mg/kg (rat)	15380 mg/kg (rabbit)	4000 ppm, vapour, 4 h (rat)
Naphthalene CAS 91-20-3	490 mg/kg (rat)	>20000 mg/kg (rabbit)	Not listed
Nonane CAS 111-84-2	Not Listed	Not listed	3200 ppm, 4 h (rat)
Trimethylbenzenes CAS 526-73-8, 95-63-6, 108-67-8	>5000 mg/kg (rat)	3160 mg/kg (rabbit)	18 mg/L vapour, 4 h (rat)
Toluene CAS 108-88-3	5580 mg/kg (rat)	12215 mg/kg (rabbit)	7585 ppm, mist, 4 h (rat)
Xylene CAS 1330-20-7	4300 mg/kg (rat)	1700 mg/kg (rabbit)	5000 ppm, 4 h (rat)

Information on likely sources of exposure

Ingestion Skin corrosion/irritation Inhalation Serious eye damage/irritation May cause stomach pains, nausea, diarrhea other delayed effects. May causes skin irritation and other allergic reactions May cause respiratory irritation, drowsiness, or dizziness. May cause serious eye damage or irritation with redness, swelling pain or blindness

Page 6 of 7

ACCUSOLVE 875 SDS GHS

Delayed and immediate effects and chronic effects from short and long-term exposure

Respiratory or skin sensitization Germ cell mutagenicity	Causes drying of the affected area and dermatitis May cause genetic defects.
Carcinogenicity	Exposure to certain chemicals found in Stoddard solvent, naphtha (petroleum), light aromatic increases
Carcinogenicity	the risk of developing certain cancers.
Reproductive toxicity	None known.
STOT - single exposure	Exposure to Stoddard solvent and naphtha (petroleum), light aromatic may cause respiratory irritation and drowsiness/dizziness. This effect is not expected to be permanent.
Aspiration Hazard	Stoddard solvent and naphtha (petroleum), light aromatic, may be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics.

Skin and eye irritation. Possible delayed effects due to prolonged or repeated skin exposure. Ingestion may cause irritation or a burning sensation of the mouth and throat, abdominal pain accompanied by nausea, vomiting, and diarrhea. Inhalation may cause irritation of nose, mouth, and upper respiratory tract, coughing, difficulty breathing, as well as headaches dizziness or nausea at high concentrations.

12. ECOLOGICAL INFORMATION

Persistence and degradability

Expected to be biodegradable

Bioaccumulative potential No information available.

<u>Mobility in soil</u> No information available

Other adverse effects This product contains ingredients that are hazardous to aquatic life. Do

I his product contains ingredients that are hazardous to aquatic life. Do not release into natural waters.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with local regulations.

Contaminated Packaging

Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

UN Number:	1993
UN Proper Shipping Name:	Flammable liquid N.O.S. (petroleum distillates)
Transport Hazard Class(es)	
Class:	TDG: 3
	US DOT: 3
	IMDG: 3
Label(s):	3
Packing Group:	III
Marine Pollutant:	No

Special precautions for user: None established

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not determined.

15. REGULATORY INFORMATION

Canada (DSL/NDSL)

All ingredients contained in this product are in compliance with the Canadian Environmental Protection Act and are listed on the DSL or are exempt.

United States (TSCA)

All ingredients contained in this product are listed on the TSCA inventory or are exempt.

ACCUSOLVE 875

ACCUSOLVE 875 SDS GHS

Page 7 of 7

16. OTHER INFORMATION

Preparation Date Revision Date Revision Note July 6, 2023 July 7, 2025 Emergency contact information updated

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet