

ACCUCLEAN 275

ALKALINE DEGREASER

AccuCLEAN 275 is a versatile, phosphate-free cleaner and degreaser designed to tackle a wide range of oily and greasy industrial soils found on walls, floors, oil rigs and other hard surfaces.

AccuCLEAN 275 is ideal for removing diesel exhaust and smoke stains found on workshop or wash bay walls.

AccuCLEAN 275 is also a very effective presoak for carwash applications, where it rapidly penetrates and lifts road grime.

FEATURES & BENEFITS

- Highly active formula
- · High foaming and easy rinsing product
- Safe for all types of pressure washers and foamers
- Phosphate free
- Versatile; suitable for cleaning walls, floors, equipment and motor vehicles
- Effective presoak in car and truck wash applications



DIRECTIONS FOR USE

Use procedure

Apply the solution to the soiled area using a low-pressure spray or foam applicator. Allow sufficient time to loosen tough soils. For particularly stubborn grime, a gentle brushing may be necessary. Rinse surface thoroughly with water. To prevent damage, do not allow **AccuClean 275** solution to dry on glass or painted surfaces.

Concentration

Full strength or 5:1 to 10:1 for heavy-duty degreasing and foaming applications 100:1 for cleaning glass or painted surfaces

Use temperature

Can be used in both hot and cold-water cleaning applications. For best results, hot water $(50^{\circ}\text{C} - 60^{\circ}\text{C} / 120^{\circ}\text{F} - 140^{\circ}\text{F})$ is recommended.

Rinsing

High pressure hot water is recommended.

ACCUCLEAN 275 ALKALINE DEGREASER

PHYSICAL PROPERTIES

Appearence

Odour

Specific gravity @ 20°C

Viscosity

pН

Flash point (TCC)

Water solubility

Boiling point

Freezing point

Foaming tendency

Concentration monitoring techniques

Rinsing

Clear, red liquid
Mild, detergent
1.072-1.092
Not available
12.0 – 13.0 (10% v/v solution in water)
None
Complete
Approx. 100°C (212°F)
Approx. 0°C (32°F)
High

Electrical conductivity, titration

Excellent

INCOMPATIBILITY

Aluminium, magnesium, tin and other soft metals, strong oxidizing agents, acids

WAREHOUSING PRECAUTIONS

Store away from incompatible materials
Keep from freezing

AVAILABLE SIZES 20L 115L 205L 1000L



IMPORTANT

Before using **ACCUCLEAN 275** always be sure to read and follow precautions and directions for use appearing on the product's container label, and on the safety data sheet (S.D.S).

FIRST AID MEASURES

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician immediately.

Skin contact

Take off contaminated clothing and rinse skin with plenty of water. Wash any contaminated clothing before re-use. Call a doctor/physician.

Inhalation

If difficulties occur after mist/vapors/spray has been inhaled, remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.

Ingestion

Do not induce vomiting unless directed by medical personnel. Rinse mouth with water and drink 1 or 2 glasses of water and call a POISON CENTER or doctor/physician immediately.

PERSONAL PROTECTION















MONTREAL

10,900 rue Secant Anjou, QC H1J 1S5 Tel.: 514-355-4660 Toll free : 1 800-361-8927

EDMONTON

11411-160 Street Edmonton, Alberta T5M 3T7 Tel.: 780-454-3919 Toll free : 1 866-454-3919