

# ACCUTREAT 775

## HARDNESS AND SCALE CONTROL ADDITIVE

**AccuTreat 775** is a hardness and scale control additive for steam boilers or compact steam generator systems that are fed with softened water.

**AccuTreat 775** contains polymeric dispersants and sequestrants that effectively inhibit scaling and prevent the deposition of suspended solids including iron oxides within the boiler.

AccuTreat 775 should be applied as part of a complete treatment program along with an oxygen scavenger such as AccuTreat 520 and a condensate line corrosion inhibitor like AccuTreat 420.

## **FEATURES AND BENEFITS**

 Contains polymeric scale inhibitors and dispersants, as well as organophosphate chelators that sequester calcium and magnesium hardness ions



# DIRECTION FOR USE

**Use procedure** 

To control scale in steam boiler systems, **Accutreat 775** should be dosed into the feedwater at a rate that will depend on the residual feedwater hardness and the percentage condensate return.

**AccuTreat 775** may be diluted with water and fed to the system proportional to feedwater rate along with other boiler water treatment chemicals using a chemical metering pump.

Additional testing for pH, alkalinity and total dissolved solids are routinely carried out to ensure that the boiler operating parameters are in accordance with the normal ranges for the successful operation of a scale and corrosion control program.

## ACCUTREAT 775 HARDNESS AND SCALE CONTROL ADDITIVE

## PHYSICAL PROPERTIES

**Appearence** 

Odour

Specific gravity @ 20°C

**Viscosity** 

pН

Flash point (TCC)

Water solubility

**Boiling point** 

Freezing point

**Foaming tendency** 

**Concentration monitoring techniques** 

Clear, colorless liquid		
Odorless		
1.163 - 1.183		
Not available		
12.0 - 14.0		
None		
Complete		
Approx. 100°C (212°F)		
Aprox. 0°C (32°F)		
Non-foaming		
Phosphonate testing kit		

### **INCOMPATIBILITY**

Strong oxidizing agents, acids

## **WAREHOUSING PRECAUTIONS**

Store away from incompatible materials
Keep from freezing

AVAILABLE SIZES				
205L				

### **IMPORTANT**

Before using **ACCUTREAT 775** always be sure to read and follow precautions and directions for use appearing on the product's container label, and on the safety data sheet (S.D.S).

## FIRST AID MEASURES

### Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician immediately.

#### Skin contact

Take off contaminated clothing and rinse skin with plenty of water. If skin irritation occurs, get medical advice/attention. Wash any contaminated clothing before reuse.

## Inhalation

If difficulties occur after mist/vapors/spray has been inhaled, remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

## Ingestion

Do not induce vomiting unless directed by medical personnel. Rinse mouth with water and drink 1 or 2 glasses of water and call a POISON CENTER or doctor/physician immediately.

# PERSONAL PROTECTION













#### MONTREAL

10,900 Secant Street Anjou, QC H1J 1S5 Tel.: 514-355-4660 Toll free : 1 800-361-8927

#### **EDMONTON**

11411-160 Street Edmonton, Alberta T5M 3T7 Tel.: 780-454-3919 Toll free : 1 866-454-3919