

AccuTREAT 920

COOLING WATER CORROSION AND SCALE INHIBITOR

AccuTREAT 920 is formulated to prevent scale deposition and control corrosion in open recirculating cooling water systems.

AccuTREAT 920 additives to protect both ferrous and non-ferrous metals against corrosion, by forming passivating barriers on metal surfaces. The polymeric scale inhibitors and dispersants in **AccuTREAT 920** bind to hardness minerals and suspended solids to prevent deposition on working surfaces.

AccuTREAT 920 should be used along with a non oxidizing biocide such as **AccuTREAT 830**, to prevent algae and pathogenic bacteria growth in the cooling water system.

FEATURES AND BENEFITS

- Multiple lines of defense against scaling and corrosion
- Contains chelators, sequestrants and polymeric dispersants to minimize control of solids on boiler surfaces
- Maintains boiler alkalinity at optimum range to prevent corrosion and reduce boiler carryover



DIRECTION FOR USE

Use procedure

AccuTREAT 920 may be pre-diluted to any convenient strength and fed to the system proportional to feedwater flow rate with chemical metering pump.

The concentration of **AccuTREAT 920** in the system should typically be maintained at 500 parts per million (ppm), to control corrosion and prevent scale deposition. The precise dosage for an individual system will depend on the potential for corrosion or scaling tendency in the circulating water.

ACCUTREAT 920

COOLING WATER CORROSION AND SCALE INHIBITOR

PHYSICAL PROPERTIES

Appearance	Clear, colorless liquid
Odour	Odorless
Specific gravity @ 20°C	1.108-1.128
Viscosity	Not available
pH	12.0 – 13.0 (10% v/v solution in water)
Flash point (TCC)	None
Water solubility	Complete
Boiling point	Approx. 100°C (212°F)
Freezing point	< 0°C (32°F)
Foaming tendency	Non-foaming
Concentration monitoring techniques	Orthophosphate or phosphonate test kit
Rinsing	Not applicable

INCOMPATIBILITY

Aluminum, tin, zinc, magnesium and other soft metals/alloys, strong oxidizing agents, acids

WAREHOUSING PRECAUTIONS

Store away from incompatible materials
Keep from freezing

AVAILABLE SIZES

			
20L	205L		

IMPORTANT

Before using **ACCUTREAT 920** always be sure to read and follow precautions and directions for use appearing on the product's container label, and on the safety data sheet (S.D.S).

FIRST AID MEASURES

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician immediately.

Skin contact

Take off contaminated clothing and rinse skin with plenty of water. Get medical advice/attention. Wash any contaminated clothing before re-use.

Inhalation

If difficulties occur after mist/vapors/spray has been inhaled, remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.

Ingestion

Do not induce vomiting unless directed by medical personnel. Rinse mouth with water and drink 1 or 2 glasses of water and call a POISON CENTER or doctor/physician immediately.

PERSONAL PROTECTION



WHMIS



MONTREAL

10,900 Secant Street
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free : 1 800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free : 1 866-454-3919