

1. IDENTIFICATION

Product Identifier

Product Name Grafikleen 212L

Recommended use of the chemical and restrictions on use

Recommended use Flexo wash
Restrictions on use For industrial use only

Supplier details

West Penetone Inc.
10900 Secant
Montreal, QC,
H1J 5S1
Tel: 514-355-4660

Emergency Telephone Number

West Penetone Inc: (514) 355-4660 8h-17h Monday to Friday
Poison Control Center (Emergency, 24 H): 1-844-POISON-X or 1-844-764-7669

2. HAZARDS IDENTIFICATION

Classification

Skin Corrosion/Irritation	Category 1
Eye damage/ irritation	Category 1

Label Elements

DANGER

Hazard Statements

Causes severe skin burns and eye damage.



Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray.
Wash face, hands and any exposed skin thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor/physician.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse.
IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
Immediately call a POISON CENTER or doctor/physician.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant according to local, provincial/federal regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Ethylene glycol monobutyl ether	111-76-2	5-10
Ethoxylated propoxylated alcohol	68603-25-8	1-5
Sodium metasilicate	6834-92-0	1-5
Sodium xylene sulfonate	1300-72-7	1-5

4. FIRST AID MEASURES**Eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Skin contact

Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

Inhalation

Remove person to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Ingestion

Do not induce vomiting. Drink 1 or 2 glasses of water. Call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Causes burns to eyes, skin and mucous membranes. Symptoms include tingling sensation and / or reddening of tissues.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

None.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Environmental Precautions

Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Handling Avoid contact with skin, eyes and clothing.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Materials Strong acids

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Only constituents with exposure limits are listed. Any constituent not listed has no known exposure limit.

Chemical Name	ACGIH TLV
Ethylene glycol monobutyl ether 111-76-2	TWA: 20 ppm

Appropriate engineering controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face Protection Safety goggles.

Skin and body protection Wear rubber or neoprene gloves.

Respiratory Protection If exposure limits are exceeded or if ventilation is inadequate, NIOSH/MSHA approved respiratory protection should be worn.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE :

Clear, yellow liquid

ODOR

Butyl solvent

ODOR THRESHOLD :

Not applicable

pH :

13

VAPOR PRESSURE, mm Hg AT 20°C :

Not applicable

VAPOR DENSITY (Air = 1) :

Not applicable

RELATIVE DENSITY AT 20°C:

1.04

SOLUBILITY IN WATER :

Complete

MELTING POINT / FREEZING POINT :

Not available

BOILING POINT/BOILING RANGE :

100 °C

FLASH POINT :

None

EVAPORATION RATE, water = 1 :

1

FLAMMABILITY (SOLID, GAS):

Not applicable

PARTITION COEFFICIENT, N-OCTANOL/WATER :

Not available

AUTO-IGNITION TEMPERATURE :

None

DECOMPOSITION TEMPERATURE:

Not available

VISCOSITY:

<10 cps

FLAMMABLE LIMITS :**UPPER:** Not applicable **LOWER :** Not applicable**10. STABILITY AND REACTIVITY****Reactivity**

Not reactive

Conditions to Avoid

Store away from incompatible materials.

Chemical Stability

Stable under normal conditions.

Possibility of hazardous reactions

None

Incompatible Materials

Strong acids

Hazardous decomposition products

None

11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Sodium metasilicate 6834-92-0	600 mg/kg (Rat)	No data available	Not applicable
Ethoxylated propoxylated alcohol 68603-25-8	> 2 g/kg (Rat)	No data available	Not applicable
Ethylene glycol monobutyl ether 111-76-2	1300 mg/kg (Rat)	> 2 g/kg (Rat)	450 ppm (rat) – 4 hours
Sodium xylene sulfonate 1300-72-7	7200 mg/kg (Rat)	Not available	Not applicable

Information on likely sources of exposure**Serious eye damage/irritation**

Corrosive to eyes and may cause grave lesions.

Skin corrosion/irritation

Corrosive to skin.

Ingestion

Ingestion may cause burns to the digestive and respiratory tract.

Inhalation

Spray mist may cause irritation or burns to respiratory tract.

Delayed and immediate effects and also chronic effects from short and long-term exposure**Respiratory or skin sensitization**

Not a sensitizer.

Germ cell mutagenicity

None known.

Carcinogenicity

No listed human carcinogens.

Reproductive toxicity

None known.

STOT - single exposure

None known.

STOT-repeated exposure

None known.

Aspiration Hazard

None.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms include tingling sensation and / or reddening of tissues, eventually leading to burn lesions.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

No information available

Persistence and degradability

No information available

Bioaccumulative potential

No information available

Mobility in soil

No information available

Other adverse effects

None known

13. DISPOSAL CONSIDERATIONS**Waste Disposal Method**

Dispose of in accordance with local regulations.

Contaminated Packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

14. TRANSPORT INFORMATION**TDG classification**

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium metasilicate), class 8, PG III

15. REGULATORY INFORMATION

All ingredients are listed on the DSL

16. OTHER INFORMATION**Preparation Date**

January 2, 2017

Revision Date

July 1, 2025

Revision Note

Updated emergency telephone number

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS