

SAFETY DATA SHEET

GRAFIKLEEN 212L

Page 1 of 5 Date prepared: January 2, 2017 MSDS : Grafikleen 212L SDS GHS

1. IDENTIFICATION

Product	Identifier
Product	Name

Grafikleen 212L

Recommended use of the chemical and restrictions on useRecommended useFlexo washRestrictions on useFor industrial use only

Supplier details

West Penetone Inc. 10900 Secant Montreal, QC, H1J 5S1 Tel: 514-355-4660

Emergency Telephone Number

Canutec (613)-996-6666

2. HAZARDS IDENTIFICATION

Classification

Skin Corrosion/Irritation	Category 1
Eye damage/ irritation	Category 1

Label Elements

DANGER

Hazard Statements Causes severe skin burns and eye damage.



Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse.

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant according to local, provincial/federal regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Ethylene glycol monobutyl ether	111-76-2	5-10
Ethoxylated propoxylated alcohol	68603-25-8	1-5
Sodium metasilicate	6834-92-0	1-5
Sodium xylene sulfonate	1300-72-7	1-5

4. FIRST AID MEASURES

Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
Skin contact	Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.
Inhalation	Remove person to fresh air and keep at rest in a position comfortable for breathing Immediately call a POISON CENTER or doctor/physician.
Ingestion	Do not induce vomiting. Drink 1 or 2 glasses of water. Call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Causes burns to eyes, skin and mucous membranes. Symptoms include tingling sensation and / or reddening of tissues.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

None.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Environmental Precautions

Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Handling

Avoid contact with skin, eyes and clothing.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Materials

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Only constituents with exposure limits are listed. Any constituent not listed has no known exposure limit.

Strong acids

Chemical Name	ACGIH TLV
Ethylene glycol monobutyl ether	TWA: 20 ppm
111-76-2	

Appropriate engineering controls

Engineering ControlsEnsure adequate ventilation, especially in confined areas.Individual protection measures, such as personal protective equipmentEye/face ProtectionSafety goggles.Skin and body protectionWear rubber or neoprene gloves.Respiratory ProtectionIf exposure limits are exceeded or if ventilation is inadequate, NIOSH/MSHA approved
respiratory protection should be worn.General Hygiene ConsiderationsHandle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE : Clear, yellow liquid ODOR Butyl solvent ODOR THRESHOLD : Not applicable pH : 13 VAPOR PRESSURE, mm Hg AT 20°C : Not applicable VAPOR DENSITY (Air = 1) : Not applicable RELATIVE DENSITY AT 20°C: 1.04 SOLUBILITY IN WATER : Complete

GRAFIKLEEN 212L

Page 4 of 5 Date prepared: January 2, 2017 MSDS : Grafikleen 212L SDS GHS

MELTING POINT / FREEZING POINT : Not available BOILING POINT/BOILING RANGE : 100 °C FLASH POINT : None EVAPORATION RATE, water = 1 : 1 FLAMMABILITY (SOLID, GAS): Not applicable PARTITION COEFFICIENT, N-OCTANOL/WATER : Not available AUTO-IGNITION TEMPERATURE : None DECOMPOSITION TEMPERATURE: Not available VISCOSITY: <10 cps FLAMMABLE LIMITS : UPPER: Not applicable LOWER : Not applicable

10. STABILITY AND REACTIVITY

Reactivity

Not reactive

Chemical Stability

Stable under normal conditions.

Incompatible Materials

Strong acids

<u>Conditions to Avoid</u> Store away from incompatible materials.

Possibility of hazardous reactions None

Hazardous decomposition products None

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Sodium metasilicate 6834-92-0	600 mg/kg (Rat)	No data available	Not applicable
Ethoxylated propoxylated alcohol 68603-25-8	> 2 g/kg (Rat)	No data available	Not applicable
Ethylene glycol monobutyl ether 111-76-2	1300 mg/kg (Rat)	> 2 g/kg (Rat)	450 ppm (rat) – 4 hours
Sodium xylene sulfonate 1300-72-7	7200 mg/kg (Rat)	Not available	Not applicable

Information on likely sources of exposure

Serious eye damage/irritation	Corrosive to eyes and may cause grave lesions.
Skin corrosion/irritation	Corrosive to skin.
Ingestion	Ingestion may cause burns to the digestive and respiratory tract.
Inhalation	Spray mist may cause irritation or burns to respiratory tract.

Delayed and immediate effects and also chronic effects from short and long-term exposure

Respiratory or skin sensitization	Not
Germ cell mutagenicity	No
Carcinogenicity	No
Reproductive toxicity	Nor
STOT - single exposure	No
STOT-repeated exposure	No
Aspiration Hazard	Noi

Not a sensitizer. None known. No listed human carcinogens. None known. None known. None known. None.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms include tingling sensation and / or reddening of tissues, eventually leading to burn lesions.

12. ECOLOGICAL INFORMATION

Ecotoxicity No information available

Persistence and degradability No information available

Mobility in soil No information available **Bioaccumulative potential** No information available

Other adverse effects None known

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with local regulations.

Contaminated Packaging

.

Empty containers should be taken for local recycling, recovery or waste disposal.

14. TRANSPORT INFORMATION

TDG classification

UN3266, corrosive liquid, basic, inorganic, n.o.s. (sodium metasilicate), class 8, PG III

15. REGULATORY INFORMATION

All ingredients are listed on the DSL

16. OTHER INFORMATION

Preparation Date Revision Date Revision Note January 2, 2017 not applicable not applicable

<u>Disclaimer</u>

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS