

## HD-2

## Heavy-duty low odour solvent cleaner

**HD-2** is a high distillate grade solvent blend designed for shop or enclosed space degreasing.

**HD-2** provides a longer dwell time for removing stubborn foulant such as bitumen and asphaltenes from lines, vessel parts, and other refinery equipment by minimizing the evaporative loss associated with the use of xylene and toluene.

## **FEATURES & BENEFITS**

- Disperses hydrocarbon sludge and foulant accumulation upon application and rinsing
- · Contains no added xylene or toluene
- Low odor alternative to the product RAMSOL
- Safe on all hard metal surfaces
- Rinses effectively leaving little to no residue
- Provides longer dwell time for improved foulant removal



# DIRECTIONS FOR USE

Soils to be removed

Tars, lubricating oils, bituminous residue, heavy oils, asphaltic materials, etc.

Use procedure

Use **HD-2** as part of a manual or low-pressure application. For very thick accumulations, physically remove excess or loose deposits before application.

Concentration

Most effective when used undiluted. Forms stable emulsion when diluted 5 to 20% v/v with water, for procedures requiring or having the need for applied heat.

**Dwell time/Operation time** 

5 to 30 minutes, according to the amount of soil.

**Mechanical action** 

Scrubbing and wiping recommended to remove stubborn deposits.

Rinsing

Allow product to dwell before rinsing. High-pressure, hot water is recommended.

# PHYSICAL PROPERTIES

**Appearence** 

Odour

Specific gravity @ 20°C

Viscosity

рΗ

Flash point (TCC)

Water solubility

**Boiling point** 

Freezing point

Foaming tendency

Rinsing

**Concentration monitoring techniques** 

Clear, yellow liquid
Solvent
0.870-0.880
Approx. 0.7 mPa/S at 38°C
Not applicable
41°C (105.8°F)
Emulsifies
Approx. 160-170°C (320-338°F)
Approx14°C (6.8°F)

#### **INCOMPATIBILITY**

Acids, strong oxidizing agents

#### **WAREHOUSING PRECAUTIONS**

Keep containers tightly closed away from direct sunlight in a dry, cool and well-ventilated place

# AVAILABLE SIZES 20L 205L 1000L

## **IMPORTANT**

Before using **HD-2** always be sure to read and follow precautions and directions for use appearing on the product's container label, and on the safety data sheet (S.D.S).

Non-foaming

Not available

Excellent

## FIRST AID MEASURES

## Eye contact

Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

## Skin contact

Wash with plenty of soap and water. If skin irritation occurs, get medical advice/ attention. Take off contaminated clothing and wash before reuse.

## Inhalation

If difficulties occur after mist/vapors/spray has been inhaled, remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

## Ingestion

Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

# PERSONAL PROTECTION



















## MONTREAL

10,900 rue Secant Anjou, QC H1J 1S5 Tel.: 514-355-4660 Toll free : 1 800-361-8927

### **EDMONTON**

11411-160 Street Edmonton, Alberta T5M 3T7 Tel.: 780-454-3919 Toll free: 1 866-454-3919 May 9, 2022