

IRON SULFIDE DISSOLVER OSP-1

ONE-STEP IRON SULFIDE REMEDIATION

IRON SULFIDE DISSOLVER OSP-1 is a fully-formulated remediation product designed to remove both pyrophoric and non-pyrophoric iron sulfide mineral deposits, entrapped in hydrocarbon fouling or within an aggressive hydrocarbon matrix, without the associated acid gas emissions.

IRON SULFIDE DISSOLVER OSP-1 effectively chelates iron sulfide minerals and emulsifies hydrocarbon foulant to provide vessel or unit entry with reduced decontamination times.

IRON SULFIDE DISSOLVER OSP-1 will assist in mitigating small concentrations of hydrogen sulfide gas.

FEATURES & BENEFITS

- Non-hazardous
- Non-combustible
- Contains added corrosion inhibitor
- Product coloration changes with saturation
- Wastewater friendly
- Low toxicity when applied
- Readily biodegradable
- Easily diluted to desired concentration in most types of water



DIRECTIONS FOR USE

Use procedure

Use **IRON SULFIDE DISSOLVER OSP-1** as part of a chemical circulation procedure via direct injection into a water-vapor or liquid stream. Consult with your local West Penetone sales representative for procedures that are best suited for your application.

Concentration

Preliminary recommendations include applications at concentrations of 40-50% v/v aqueous dilution for most remediation procedures. Most effective when used at full concentration.

Use temperature

Ambient up to 60°C (140°F). Most effective at higher temperatures.

Dwell time / Operation time

Dependent on job, site and method of application. Dwell time may vary from 6-10 hours depending on depth of scaling and degree of contamination. Retain monitoring is recommended.

IRON SULFIDE DISSOLVER OSP-1

ONE-STEP
IRON SULFIDE REMEDIATION

PHYSICAL PROPERTIES

Appearance	Clear, yellow liquid
Odour	Acidic
Specific gravity @ 20 °C	1.090
Viscosity	Not available
pH	4.0-5.0
Flash point (TCC)	None
Water solubility	Complete
Boiling point	Not available
Freezing point	Not available
Foaming tendency	High
Rinsing	Excellent
Concentration monitoring techniques	Titration

INCOMPATIBILITY

Strong oxidizing, reducing
or alkaline materials

WAREHOUSING PRECAUTIONS

Keep containers tightly closed away
from direct sunlight in a dry,
cool and well-ventilated place

AVAILABLE SIZES

			
		205L	

IMPORTANT

Before using **IRON SULFIDE DISSOLVER OSP-1**, always be sure to read and follow precautions and directions for use appearing on the product's container label, and on the safety data sheet (S.D.S).

FIRST AID MEASURES

Ingestion

Do NOT induce vomiting. Drink 1 or 2 glasses of water. Call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person.

Skin contact

Wash with plenty of water. If skin irritation or rash occurs, get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

PERSONAL PROTECTION



WHMIS



MONTREAL

10,900 rue Secant
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free : 1 800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free : 1 866-454-3919