

SAFETY DATA SHEET

LIQUID DYNEMATE PLUS

Page 1 of 5

Date prepared: January 2, 2017

MSDS: Liq Dynemate Plus SDS GHS

1. IDENTIFICATION

Product Identifier

Product Name Liquid Dynemate Plus

Recommended use of the chemical and restrictions on use

Recommended use Chlorinated alkaline cleaner Restrictions on use Do not mix with acids

Supplier details

West Penetone Inc. 10900 Secant Montreal, QC, H1J 5S1

Tel: 514-355-4660

Emergency Telephone Number

Canutec (613)-996-6666

2. HAZARDS IDENTIFICATION

Classification

Skin Corrosion/Irritation	Category 1
Eye damage/ irritation	Category 1
Acute oral toxicity	Category 5
Corrosive to metals	Category 1

Label Elements

DANGER

Hazard Statements

Causes severe skin burns and eye damage.

May be corrosive to metals. May be harmful if swallowed.



Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash face, hands and any exposed skin thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Keep only in original packaging.

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse.

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Absorb spillage to prevent material damage.

Page 2 of 5

Date prepared: January 2, 2017 MSDS: Lig Dynemate Plus SDS GHS

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant according to local, provincial/federal regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Potassium hydroxide	1310-58-3	10-15
Sodium tripolyphosphate	7758-29-4	5-10
Sodium hypochlorite	7681-52-9	1-5
Potassium silicate	1312-76-1	1-5

4. FIRST AID MEASURES

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Skin contact Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Wash contaminated clothing before reuse.

Inhalation Remove person to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor/physician.

Ingestion Do not induce vomiting. Drink 1 or 2 glasses of water. Call a physician or Poison Control

Centre immediately. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Causes burns to eyes, skin and mucous membranes. Symptoms include tingling sensation and / or reddening of tissues.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

None.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

LIQUID DYNEMATE PLUS Page 3 of 5

Date prepared: January 2, 2017 MSDS: Liq Dynemate Plus SDS GHS

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Environmental Precautions

Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Handling Avoid contact with skin, eyes and clothing.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Materials Acids

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Only constituents with exposure limits are listed. Any constituent not listed has no known exposure limit.

Chemical Name	ACGIH TLV	
Potassium hydroxide	STEL: 2 mg/m ³	
1310-58-3		

Appropriate engineering controls

ODOR THRESHOLD:

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face Protection Safety goggles.

Skin and body protection Wear rubber or neoprene gloves, rubber apron and boots.

Respiratory Protection If exposure limits are exceeded or if ventilation is inadequate, NIOSH/MSHA approved

respiratory protection should be worn.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: VAPOR PRESSURE, mm Hg AT 20°C:

Clear, light green liquid

ODOR

Not applicable

VAPOR DENS

VAPOR DENSITY (Air = 1):

Faint chlorine Not applicable

RELATIVE DENSITY AT 20°C:

Not applicable 1.27

LIQUID DYNEMATE PLUS Page 4 of 5

Date prepared: January 2, 2017 MSDS: Liq Dynemate Plus SDS GHS

pH: SOLUBILITY IN WATER:

> 13 Complete

MELTING POINT / FREEZING POINT : PARTITION COEFFICIENT, N-OCTANOL/WATER :

Not available Not available

BOILING POINT/BOILING RANGE : AUTO-IGNITION TEMPERATURE :

100 °C None

FLASH POINT: DECOMPOSITION TEMPERATURE:

None Not available EVAPORATION RATE, water = 1 : VISCOSITY: 1 <10 cps

FLAMMABILITY (SOLID, GAS): FLAMMABLE LIMITS :

Not applicable UPPER: Not applicable LOWER: Not applicable

10. STABILITY AND REACTIVITY

Reactivity Conditions to Avoid

Not reactive Store away from incompatible materials.

<u>Chemical Stability</u> <u>Possibility of hazardous reactions</u>

Stable under normal conditions.

Chlorine gas is generated when mixed with acids.

Incompatible Materials Hazardous decomposition products

Acids None

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Potassium hydroxide 1310-58-3	365 mg/kg (Rat)	No data available	Not applicable
Sodium hypochlorite 7681-52-9	5.3 g/kg (Rat)	No data available	Not applicable
Sodium tripolyphosphate 7758-29-4	3100 mg/kg (Rat)	7940 mg/kg (Rabbit)	Not applicable
Potassium silicate 1312-76-1	1300 mg/kg (Rat)	No data available	Not applicable

Information on likely sources of exposure

Serious eye damage/irritationCorrosive to eyes and may cause grave lesions, including blindness.

Skin corrosion/irritationCorrosive to skin.

IngestionIngestion may cause burns to the digestive and respiratory tract.InhalationSpray mist may cause irritation or burns to respiratory tract.

Delayed and immediate effects and also chronic effects from short and long-term exposure

Respiratory or skin sensitization Not a sensitizer. Germ cell mutagenicity None known.

Carcinogenicity No listed human carcinogens.

Reproductive toxicity None known.

STOT - single exposure No information available. STOT-repeated exposure No information available.

Aspiration Hazard None.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms include tingling sensation and / or reddening of tissues, eventually leading to burn lesions.

LIQUID DYNEMATE PLUS Page 5 of 5

Date prepared: January 2, 2017 MSDS: Liq Dynemate Plus SDS GHS

12. ECOLOGICAL INFORMATION

Ecotoxicity

No information available

Persistence and degradability Bioaccumulative potential

No information available None known

Mobility in soil Other adverse effects

No information available None known

13. DISPOSAL CONSIDERATIONS

<u>Waste Disposal Method</u> Dispose of in accordance with local regulations.

Contaminated Packaging Empty containers should be taken for local recycling, recovery or waste disposal.

14. TRANSPORT INFORMATION

TDG classification

UN1760, corrosive liquid n.o.s. (potassium hydroxide), class 8, PG III

15. REGULATORY INFORMATION

All ingredients are listed on the DSL

16. OTHER INFORMATION

Preparation DateJanuary 2, 2017Revision Datenot applicableRevision Notenot applicable

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS