

SAFETY DATA SHEET

SLICK LX Page 1 of 5

SLICK LX SDS GHS

1. IDENTIFICATION

Product Identifier

Product Name SLICK LX

Chemical Name Moisture displacing oil

Recommended use of the chemical and restrictions on use

Recommended use Surface lubricant and moisture displacing oil

Restrictions on use For industrial use only

Supplier details West Penetone Inc. 11411-160 Street

Edmonton, AB, T5M3T7

Tel: 780-454-3919

Emergency Telephone Number

(780) 454-3919 (Mon - Fri, 8 AM - 4:30 PM, Mountain time)

2. HAZARDS IDENTIFICATION

Classification

Flammable liquids	Category 4
Skin corrosion/irritation	Category 3
Aspiration hazard	Category 1

Label Elements

DANGER

Hazard Statements

Combustible liquid

Causes mild skin irritation

May be fatal if swallowed and enters airways





Precautionary Statements - Prevention

Keep away from heat, sparks, open flames and hot surfaces. No smoking.

Wash face, hands and any exposed skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing, and eye protection or face protection.

Precautionary Statements - Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting, Immediately call a POISON CENTER or doctor.

IF ON SKIN (or hair): Take off contaminated clothing. Rinse SKIN with water. IF SKIN irritation occurs: Get medical advice/attention.

In case of fire: Use carbon dioxide, foam, or dry chemical to extinguish.

Precautionary Statements - Storage

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant according to local, provincial/federal regulations.

SLICK LX Page 2 of 5

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight %
C9-11 alkanes/cycloalkanes	64742-48-9	30 – 60*
1-Butoxy-2-propanol	5131-66-8	0.5 – 1.5*

^{*}Actual concentration is withheld as a trade secret

4. FIRST AID MEASURES

Ingestion: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician immediately.

Skin contact: Wash with plenty of water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing

and wash before reuse.

Inhalation: If difficulties occur after mist, vapors or spray has been inhaled, remove person to fresh air and keep

comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. If eye irritation persists, get medical advice/attention.

Most important symptoms and effects, both acute and delayed.

Contact with eyes may cause mild irritation leading to discomfort. Contact with skin may cause irritation with local redness and possible dermatitis with prolonged ore repeated exposure. Inhalation of vapors may cause drowsiness or dizziness, headaches, fatigue, muscular weakness and in extreme cases, loss of consciousness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion may cause pneumonitis or pulmonary edema if aspirated.

Indication of any immediate medical attention and special treatment needed.

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use water fog, foam, dry chemical, or carbon dioxide to extinguish flames.

Unsuitable Extinguishing Media

Do not use water jet.

Specific hazards arising from the chemical.

During fire, gases hazardous to health may be formed including oxides of carbon, nitrogen and sulfur.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Use personal protective equipment.

Environmental Precautions

Avoid discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up.

Contain and solidify with inert absorbent materials. Keep in suitable, closed containers for disposal. Following product recovery, flush area with water. For large spills, stop flow of material, prevent product from entering drains, and pump off product where this is without risk and possible. Proceed as above. Spills will create very slippery conditions.

SLICK LX Page 3 of 5

SLICK LX SDS GHS

7. HANDLING AND STORAGE

Precautions for Safe Handling

Handling: Avoid inhalation of mist, vapors or spray. Avoid contact with skin, eyes and clothing. Ensure thorough

ventilation of work areas. Use personal protective equipment. Keep away from sources of ignition.

Smoking should be prohibited in the application area

Conditions for safe storage, including any incompatibilities

Storage: Keep containers tightly closed away in a dry, cool and well-ventilated place, away from incompatible

materials.

Incompatible Materials: Strong oxidizing agents, concentrated alkalis, and concentrated mineral acids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Only constituents with exposure limits are listed. Any constituent not listed has no known exposure limit.

Appropriate engineering controls

Engineering Controls: Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face Protection: Safety glasses with side shields or goggles. Use a face-shield where mode of handling

increases risk of splashing.

Skin and body protection: Wear protective gloves and protective clothing.

Respiratory Protection: Wear respiratory protection if ventilation is inadequate.

General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice. Routinely wash work

clothing and protective equipment to remove contaminants.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: VAPOR PRESSURE, mm Hg AT 20°C:

Yellow to brown liquid Not available

ODOR: **VAPOR DENSITY (Air = 1):** Mild, musty Not available

ODOR THRESHOLD: RELATIVE DENSITY AT 20°C:

Not available 0.840-0.860

pH: **SOLUBILITY IN WATER:**

Not applicable Insoluble

MELTING POINT / FREEZING POINT: PARTITION COEFFICIENT, N-OCTANOL/WATER: Not available Not available

BOILING POINT/BOILING RANGE: AUTO-IGNITION TEMPERATURE:

>180°C Not available **FLASH POINT:**

DECOMPOSITION TEMPERATURE:

69°C / 156°F Not available **EVAPORATION RATE**, water = 1: VISCOSITY: Not available

FLAMMABILITY (SOLID, GAS): FLAMMABLE LIMITS:

Not applicable Not available SLICK LX Page 4 of 5

SLICK LX SDS GHS

10. STABILITY AND REACTIVITY

Reactivity

Not reactive.

Chemical Stability

Stable under normal conditions.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to Avoid

Avoid extreme temperatures. Store away from incompatible materials.

Incompatible Materials

Strong oxidizing agents, concentrated alkalis, and concentrated mineral acids.

<u>Hazardous decomposition products</u>

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition can lead to release of irritating gases and vapors such as oxides of carbon as well as other low molecular weight hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

 $\underline{\mathsf{ATE}_{\mathsf{mix}}}$ – LD50 oral >5000 mg/kg (rat), LD50 dermal >5000 mg/kg (rabbit), LC50 inhalation >10 mg/L – 4 h (rat) Not classified as an acutely toxic mixture.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
C9-11 alkanes/cycloalkanes CAS 64742-48-9	>5000 mg/kg (rat)	Not available	Not available
1-Butoxy-2-propanol CAS 5131-66-8	3300 mg/kg (rat)	>5000 mg/kg (rat)	> 3.5 mg/l 4 h, vapour (rat)

Information on likely sources of exposure

Ingestion May cause stomach pains, nausea, diarrhea other delayed effects. May be fatal if liquid enters airways.

Skin corrosion/irritation May causes mild skin irritation, possible dermatitis with prolonged exposure

Inhalation May cause respiratory irritation, drowsiness, or dizziness. May be fatal if liquid enters airways.

Serious eye damage/irritation May cause mild eye irritation.

Delayed and immediate effects and chronic effects from short and long-term exposure

Respiratory or skin sensitization
Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
None known
None known
None known
None known

Aspiration Hazard C9-11 alkanes/cycloalkanes (CAS 64742-48-9) May be fatal if swallowed and enters airways

Symptoms related to the physical, chemical and toxicological characteristics.

Skin and eye irritation. Possible delayed effects due to prolonged or repeated skin exposure. Ingestion may cause irritation or of the mouth and throat, abdominal pain accompanied by nausea, vomiting, and diarrhea. Inhalation may cause irritation of nose, mouth, and upper respiratory tract, coughing, difficulty breathing, as well as headaches dizziness or nausea at high concentrations. If the liquid enters airways, breathing difficulties may occur.

SLICK LX Page 5 of 5

SLICK LX SDS GHS

12. ECOLOGICAL INFORMATION

Persistence and degradabilityBioaccumulative potentialExpected to be readily biodegradableNo information available.

Mobility in soil Other adverse effects

No information available

This product contains ingredients that are harmful to aquatic life. Do

not release into natural waters.

13. DISPOSAL CONSIDERATIONS

<u>Waste Disposal Method</u> Dispose of in accordance with local regulations.

Contaminated Packaging Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

UN Number: Not regulated UN Proper Shipping Name: Not regulated

Transport Hazard Class(es)

Class: TDG: Not regulated

US DOT: Not regulated IMDG: Not regulated Not regulated

Label(s): Not regulated Packing Group: Not regulated

Marine Pollutant: No .

Special precautions for user: None established

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not determined.

15. REGULATORY INFORMATION

Canada (DSL/NDSL)

All ingredients contained in this product are in compliance with the Canadian Environmental Protection Act and are listed on the DSL or are exempt.

16. OTHER INFORMATION

Preparation Date February 10, 2023 Revision Date July 11, 2025

Revision Note Emergency contact information updated

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.