

WESTKLEEN 4115

GENERAL PURPOSE ALKALINE DEGREASER

WESTKLEEN 4115 is a multi purpose liquid cleaner which combines the qualities of a solvent and mild alkaline detergent. It is moderately foaming and may be used manually or mechanically for medium to light duty cleaning.

WESTKLEEN 4115 is effective on a wide variety of deposits such as lubricating oils and grease, wax, printing ink, rubber marks on floors and walls.

FEATURES & BENEFITS

- Low alkalinity
- Mild odour
- Non flammable
- Completely water dilutable and forms a stable solution
- Phosphate free
- Moderate foaming
- Easy to rinse
- Environmentally and user safe
- Non-corrosive on all surfaces
- Does not interfere with water treatment systems



DIRECTIONS FOR USE

PROCEDURE #1

EQUIPMENT TO BE CLEANED

Industrial equipment, floors, walls, work tables, tools, shower stalls, printing presses.

SOILS TO BE REMOVED

Effective on a wide variety of deposits such as lubricating oils and grease, wax, printing ink, rubber marks.

USE PROCEDURE

Soak a pad or cloth and scrub surfaces to be cleaned. Rinse with water.

CONCENTRATION

1% to 5%

USE TEMPERATURE

High temperature recommended.

DWELL TIME/OPERATION TIME

Not applicable with manual cleaning.

MECHANICAL ACTION

Scrubbing with a steel pad recommended.

RINSING

Warm or hot water.

REUSE/RECYCLING

No.

PROCEDURE #2

EQUIPMENT TO BE CLEANED

Heavy industrial equipment, floors and walls, shower areas.

SOILS TO BE REMOVED

Effective on a wide variety of deposits such as lubricating oil and grease, wax, printing ink, rubber marks.

USE PROCEDURE

Inject product into the water of the high pressure (HPLV) cleaning system. Apply with high pressure then rinse with water.

CONCENTRATION

1% to 5%

USE TEMPERATURE

High 50°C recommended.

DWELL TIME/OPERATION TIME

Allow to dwell before final rinse.

MECHANICAL ACTION

Scrubbing with a steel pad recommended.

RINSING

Warm or hot water.

REUSE/RECYCLING

No.

WESTKLEEN 4115 GENERAL PURPOSE ALKALINE DEGREASER

PHYSICAL PROPERTIES

Appearance	Clear, yellow liquid
Odour	Butyl solvent
Specific gravity @ 20°C	1.04
Viscosity	<10 cps
pH	13
Flash point (TCC)	None
Water solubility	Complete
Boiling point	100°C (212°F)
Freezing point	Not available
Foaming tendency	Moderate
Rinsing	Excellent
Concentration monitoring techniques	Electrical conductivity, titration

INCOMPATIBILITY

Strong acids

WAREHOUSING PRECAUTIONS

Keep containers tightly closed away from direct sunlight in a dry, cool and well-ventilated place

AVAILABLE SIZES

			
4L	20L	205L	1000L



IMPORTANT

Before using **WESTKLEEN 4115**, always be sure to read and follow precautions and directions for use appearing on the product's container label, and on the safety data sheet (S.D.S).

FIRST AID MEASURES

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Skin contact

Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

Inhalation

Remove person to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Ingestion

Do not induce vomiting. Drink 1 or 2 glasses of water. Call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person.

PERSONAL PROTECTION



WHMIS

